



VERITAS NG SERIES



Specifications

		I/D UNIT	CHS09FTXQNG(I)	CHS12FTXQNG(I)	CHS18FTXQNG(I)	CHS24FTXL2QNG(I)
		O/D UNIT	CHS09FTXQNG(O)	CHS12FTXQNG(O)	CHS18FTXQNG(O)	CHS24FTXL2QNG(O)
		btus/hr	9,000	12,000	18,000	22,000
Cooling capacity	btus/hr		8870(1500-10236)	11942(2047-12283)	17060(2218-17742)	22007(6820-27978)
Heating capacity	btus/hr		9554(2047-10918)	12283(2047-12966)	18084(2389-18016)	22007(6820-29002)
SEER/ COP	kW		6.10 / 4.6	6.10 / 4.6	6.10 / 4.6	6.30 / 5.10
SEER class / SCOP class			A++/ A++	A++/ A++	A++/ A++	A++/ A++
I/D unit - noise levels (1m)	L, M, H	dB(A)	23/26/35	24/28/37	28/33/39	30/33/40
O/D unit - noise level	H	dB(A)	49	51	54	58
Copper piping	Liquid	mm	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas	mm	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	15.8 (5/8)
Dimensions	Indoor	mm	790x200x275	790x200x275	970x225x300	1078x246x325
	Outdoor	mm	782x596x257	848x596x257	848x596x257	890x700x340
Electrical supply on the			Outdoor	Outdoor	Outdoor	Outdoor
Energy Class			A++/ A++	A++/ A++	A++/ A++	A++/ A++
PRICE INSTALLED			€ 495.00	€ 515.00	€ 720.00	€ 895.00

Features

LED display
24hrs timer
Auto restart
Easy clean design
Self diagnosis
Sleep function mode
Blue fin coating

Standard terms

Guarantee - 5 years FULL
Price includes VAT
Includes up to 4m copper length
Extra copper at €28.00 inc. VAT
50% deposit/ balance on completion
r32 eco energy friendly
Dismantling/ safe cart away charges - €25.00



info@cooperandhunter.mt



TITAN
International Ltd

23474000